

Current Transducer RA 1005-S

For the measurement of alternating components in a determined bandwidth, contained in a continuous primary current.



Electrical data

M	Mutual inductance	$3.98 \cdot 10^{-6}$	H
U_{out}	Output voltage (instantaneous) ¹⁾	$U_{out} = M \cdot \frac{di_p}{dt}$	V
U_{out}	Output voltage (sinusoidal wave) ¹⁾	$U_{out} = 2 \cdot \pi \cdot M \cdot f \cdot I_{PAC}$	V
		with $2 \cdot \pi \cdot M = 25 \cdot 10^{-6}$	H
	Example: @ 50 Hz, 20 A $U_{out} = 2 \cdot \pi \cdot 3.98 \cdot 10^{-6} \cdot 50 \cdot 20 = 25$		mV
L_S	Inductance of secondary windings (± 3 %)	5.9	mH
N_S	Number of secondary turns	1480	

Accuracy - Dynamic performance data

BW	Frequency bandwidth	20 ... 3000	Hz
ε	Error @ $I_{PAC} = 0.1 \dots 20$ A, $T_A = 25$ °C $BW = 20 \dots 3000$ Hz	$< \pm 3$	%
φ_{or}	Rated phase offset	-90°	
φU_{out}	Phase error of output voltage $U_{out}^{(1)}$, I_p sinusoidal	$BW = 20 \dots 100$ Hz $-90^\circ \pm 5^\circ$ $BW = 100 \dots 3000$ Hz $-90^\circ \pm 2.5^\circ$	
$\frac{\Delta M_T}{M} \cdot 100$	Thermal drift of M_T	$T_A = -40 \dots + 85$ °C $< \pm 0.3$	%
$\frac{\Delta L_T}{L} \cdot 100$	Thermal drift of L_S and L_T	$T_A = -40 \dots + 85$ °C $< \pm 0.3$	%

Test circuit

L_T	Inductance of secondary winding (± 4 %)	6	mH
N_T	Number of turns (test winding)	1440	
R_T	Resistance of test winding @ $T_A = 85$ °C (± 5 %)	307	Ω
I_T	Test current	< 40	mA

General data

T_A	Ambient operating temperature	$-40 \dots 85$	°C
T_{Ast}	Ambient storage temperature	$-45 \dots 90$	°C
T_B	Primary conductor temperature	≤ 100	°C
R_S	Resistance of secondary winding @ $T_A = 85$ °C (± 4 %)	312	Ω
m	Mass	760	g
	Standards	EN 50155: 2007 EN 50121-3-2: 2015	

Note: ¹⁾ Without load resistance.

Feature

- Insulated plastic case recognized according to UL 94-V0.

Advantages

- No insertion losses
- Current overload capability.

Applications

- Single or three phase inverters
- Propulsion and braking choppers
- Propulsion converters
- Auxiliary converters
- Battery chargers.

Application Domain

- Railway (fixed installations and onboard).

Current Transducer RA 1005-S

Insulation coordination

U_d	RMS voltage for AC insulation test, 50 Hz, 1 min	12 ¹⁾	kV
		1.5 ²⁾	kV
		0.5 ³⁾	kV
U_t	Partial discharge RMS test voltage ($q_m < 10$ pC)	> 2.8 ⁴⁾	kV
d_{cp}	Creepage distance ⁵⁾	82.70	mm
d_{cl}	Clearance ⁵⁾	69.60	mm
CTI	Comparative Tracking Index (group I)	600	

Notes: ¹⁾ Between primary and secondary + test turns + shield
²⁾ Between secondary + test turns and shield
³⁾ Between secondary and test turns
⁴⁾ Test carried out with a busbar $\varnothing$ 40 mm centered in the aperture
⁵⁾ See details figure 1.

Safety

This transducer must be used in limited-energy secondary circuits according to IEC 61010-1.



This transducer must be used in electric/electronic equipment with respect to applicable standards and safety requirements in accordance with the manufacturer's operating instructions.



Caution, risk of electrical shock

When operating the transducer, certain parts of the module can carry hazardous voltage (e.g. primary busbar, power supply).

Ignoring this warning can lead to injury and/or cause serious damage.

This transducer is a build-in device, whose conducting parts must be inaccessible after installation. A protective housing or additional shield could be used.

Main supply must be able to be disconnected.

IMPORTANT NOTICE

The information in this document is considered accurate and reliable. However, LEM International SA and any company directly or indirectly controlled by LEM Holding SA ("LEM") do not provide any guarantee or warranty, expressed or implied, regarding the accuracy or completeness of this information and are not liable for any consequences resulting from its use. LEM shall not be responsible for any indirect, incidental, punitive, special, or consequential damages (including, but not limited to, lost profits, lost savings, business interruption, costs related to the removal or replacement of products, or rework charges) regardless of whether such damages arise from tort (including negligence), warranty, breach of contract, or any other legal theory.

LEM reserves the right to update the information in this document, including specifications and product descriptions, at any time without prior notice. Information in this document replaces any previous versions of this document. No license to any intellectual property is granted by LEM through this document, either explicitly or implicitly. Any Information and product described herein is subject to export control regulations.

LEM products may possess either unidentified or documented vulnerabilities. It is the sole responsibility of the purchaser to design and operate their applications and products in a manner that mitigates the impact of these vulnerabilities. LEM disclaims any liability for such vulnerabilities. Customers must select products with security features that best comply with applicable rules, regulations, and standards for their intended use. The purchaser is responsible for making final design decisions regarding its products and for ensuring compliance with all legal, regulatory, and security-related requirements, irrespective of any information or support provided by LEM.

LEM products are not intended, authorized, or warranted for use in life support, life-critical, or safety-critical systems or equipment, nor in applications where failure or malfunction of an LEM product could result in personal injury, death, or significant property or environmental damage. LEM and its suppliers do not assume liability for the inclusion and/or use of LEM products in such equipment or applications; thus, this inclusion and/or use is at the purchaser's own and sole risk. Unless explicitly stated that a specific LEM product is automotive qualified, it should not be used in automotive applications. LEM does not accept liability for the inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

Applications that are described herein are for illustrative purposes only. LEM makes no representation or warranty that LEM products will be suitable for a particular purpose, a specified use or application. The purchaser is solely responsible for the design and operation of its applications and devices using LEM products, and LEM accepts no liability for any assistance with any application or purchaser product design. It is purchaser's sole responsibility to determine whether the LEM product is suitable and fit for the purchaser's applications and products planned, as well as for the planned application and use of purchaser's third-party customer(s).

Stressing and using LEM products at or above limiting values will cause permanent damage to the LEM product and potentially to any device embedding or operating with LEM product. Limiting values are stress ratings only and operation of the LEM product at or above conditions and limits given in this document is not warranted. Continuous or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the LEM product.

LEM products are sold subject to the general terms and conditions of commercial sale, as published at www.lem.com unless otherwise agreed in a specific written agreement. LEM hereby expressly rejects the purchaser's general terms and conditions for purchasing LEM products by purchaser. Any terms and conditions contained in any document issued by the purchaser either before or after issuance of any document by LEM containing or referring to the general terms and conditions of sale are explicitly rejected and disregarded by LEM, and the document issued by the purchaser is wholly inapplicable to any sale or licensing made by LEM and is not binding in any way on LEM.

© 2025 LEM INTERNATIONAL SA – All rights reserved